

LEGANZA STONE WALL

No. TD : L-013
Revision : 01
Effective Date : 22/04/2025

PRODUCT DESCRIPTION

LEGANZA Stone Wall is a classic design decorative wall paint made from water based acrylic polymer, special aggregate and special color pigment for creative building's appearance natural stone-like and can be applied to exterior & interior wall. This product is change the wall look like as natural stone surface if touched, aesthetic and elegant stone texture.

USES

- Exterior & Interior wall
- Concrete
- GRC panel

FEATURES AND BENEFITS

- Good weather resistance
- Good fungus and mold resistance
- Lighter construction
- Faster working time
- Lower costs
- Low Odor
- Water based, No added heavy metal (lead and mercury free)
- Environmentally friendly.

PRODUCT DATA

Type	: Acrylic Emulsion Texture Paint
Color	: As shown in the color card
Finish	: Matt
Solid by volume	: $\pm 64.5 \%$
Specific gravity	: ± 1.70
Material Consumption	: 3.00 – 4.00 kg/m ² (per coat, 1200 - 1600 microns Dry Film Thickness)
	Depend on film thickness and wastage during application.
Drying time	: Surface dry = 60 minutes (30° C)
	Depend on temperature and humidity
Packaging	: 5.75 kg-set or 46 kg-set
Storage stability	: One year if stored cool and dry and in original not opened container

APPLICATION

Thinning ratio by volume	: - (ready for use)
Application tools	: Special Texture Spray Gun
Wet film thickness	: 1875 – 2485 microns (per coat)
Dry film thickness	: 1200 – 1600 microns (per coat)

Recommended dry film thickness	: 1200 – 1600 microns (1 x 1200 - 1600 microns), depend on color
Recoating Interval	: Minimum 24 hours (30° C), when the first paint film already dry Maximum -
Post treatment	: Masking tape is used to protect surface not to be painted, e.g. door and window frames. As the dry film is elastic, cut the line with a knife or a cutter before remove the masking tape.
Cleaning	: Wash all equipment immediately after use with water.

SURFACE PREPARATION

- The surface must be dry, clean, sound, and free from all contaminants. Newly build wall must be dry after 28 days old. Make sure moisture content / dampness of wall $\leq 16\%$ measured using Protimeter appliance and wall alkalinity (pH) 7 – 8 measured using Universal pH indicator.
- Remove all loose material or defective paint by thorough brushing and scraping using active fibre brush.
- Treat any areas affected by mould, algae, moss and lichens with **PROPAN Fungicidal Wash**.
- Repair defects with suitable filler. Use sand and cement mix for large holes and crack. Allow to dry.
- It is recommended to apply alkali resisting primer before applying this coating.

APPLICATION CONDITION

Temperature	: Minimum 15° C Maximum 50° C
Humidity maximum	: 80 % RH Provide adequate ventilation during application and drying

RECOMMENDED COATING SCHEDULE

- Primer coat	DECOR Alkali Resisting Primer AS – 310 without thinning, 1 x 30 microns.
- Base coat color	DECORSHIELD thinning with 1 part of clean water to 10 parts of paint, 2 - 3 x 30 microns Dry Film Thickness, depend on color.
- Finish coat	DECORSHIELD mix with LEGANZA FILLER (2,5 L : 2,5 kg or 20 L : 20 kg) without thinning, 1 x 1200 - 1600 microns Dry Film Thickness, depend on color.
- Finish coat accent (optional)	DECORSHIELD mix with LEGANZA FILLER (2,5 L : 2,5 kg or 20 L : 20 kg) without thinning, 1 x 500 microns Dry Film Thickness, as accent (depend on color).

PRECAUTION

Do not take internally. This product is non toxic and non flammable. It does not contain any material with heavy metals such as mercury and lead. Avoid contact with the skin and eyes. Higher concentrations produce more severe irritation. Wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Use barrier cream. Wash splashes from skin or eyes immediately. Read all safety, security, health and environment precautions before use.

FIRST AID

- Eye contact : Rinse immediately with plenty of clean water. Seek medical advice.
Skin contact : Wash off thoroughly with plenty of water and soap immediately.
Remove contaminated clothing. If irritation occurs, seek medical advice.
Inhalation : Remove person to fresh air, loosen collar and avoid exertion.
Keep patient rested and give artificial respiration.
Ingestion : Provide symptomatic treatment and seek medical advice

DISCLAIMER

This document contains information issued based on the best and latest of Propan's knowledge in accordance to laboratory testing and practical application experience. The end user must test the product's suitability for their specific application and purpose. Propan shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements. This document is subjected to change without further notice. Please consult Propan for any specific guidance on the suitability of this product for their needs or for any specific application practices