

DECORFLEX

ELASTOMERIC EXTERIOR WALLPAINT
DF-97

No. TD : D-013
Revision : 00
Effective Date : 06/03/2023

PRODUCT DESCRIPTION

DECORFLEX Elastomeric Exterior Wallpaint DF-97 is an elastomeric wallpaint made from elastomeric acrylic polymer that is flexible and elastic with the ultimate all weather protection.

USES

- Exterior wall
- Partition and ceiling surfaces such as brick work / cement plaster
- Concrete
- GRC panel

FEATURES AND BENEFITS

- Can cover hairline crack
- Prevent penetration of rain water into the wall
- Low dirt pick up and washable
- Anti algae & anti fungal
- Weather resistant, UV light resistant
- Good adhesion to substrates
- Low odour & VOC
- Easy to apply
- Fast drying
- Bright color and available in many beautiful colors
- Good color retention.
- No added heavy metal (lead and mercury free)
- Environmentally friendly

PRODUCT DATA

Type	: Elastomeric Acrylic Polymer
Color	: As shown in the color card
Finish	: Matt
Solid by volume	: $\pm 45.50 \%$
Specific gravity	: ± 1.38
Theoretical coverage	: $5 - 7 \text{ m}^2 / \text{liter}$ (per coat, 70 micron Dry Film Thickness) Depend on film thickness and wastage during application.
Drying time	: Surface dry = 1 hours (30° C) Depend on temperature and humidity
Packaging	: 2.5 liter, 20 liter
Storage	: The product must be stored in accordance with national regulations. Keep the container in a dry, cool, well ventilated space and away from sources of heat and ignition. Container must be kept tightly closed. Handle with care.

APPLICATION

Thinning ratio by volume	: 10 % clean water
Application tools	: Brush, Roll, Air spray or Airless spray gun
Wet film thickness	: 135 - 180 microns (per coat)
Dry film thickness	: 60 - 80 microns (per coat)
Recommended dry film thickness	: 140 microns (2 x 70 microns)
Elongation coefficient	: 200 %
Recoating interval	: Minimum 2 hours (30° C), when the first paint film already dry Maximum -
Post treatment	: Masking tape is used to protect surface not to be painted, e.g. door and window frames. As the dry film is elastic, cut the line with a knife or a cutter before remove the masking tape.
Cleaning	: Wash all equipment immediately after use with water

SURFACE PREPARATION

- The surface must be dry, clean, sound, and free from all contaminants. Newly build wall must be dry after 28 days old. Make sure moisture content / dampness of wall ≤ 16 % measured using Protimeter appliance and wall alkalinity (pH) 7 – 8 measured using Universal pH indicator.
- Remove all loose material or defective paint by thorough brushing and scraping using active fibre brush.
- Treat any areas affected by mould, algae, moss and lichens with **PROPAN Fungicidal Wash**.
- Repair defects with suitable filler. Use sand and cement mix for large holes and crack. Allow to dry.
- It is recommended to apply alkali resisting primer before applying this coating.

APPLICATION CONDITION

Temperature	: Minimum 15° C Maximum 50° C
Humidity maximum	: 80 % RH Provide adequate ventilation during application and drying.

RECOMMENDED COATING SCHEDULE

- Primer coat : DECOR Alkali Resisting Primer AR – 300 without thinning, 1 x 30 microns, or DECOR Alkali Resisting Primer AS – 310 without thinning, 1 x 30 microns (for cement plaster & concrete wall with higher level of alkaline content).
- Finish coat : DECORFLEX Elastomeric Exterior Wallpaint DF – 97 thinning with 1 part of clean water to 10 parts of paint, 2 x 70 microns Dry Film Thickness, depend on color.

SAFETY, SECURITY, HEALTH AND ENVIRONMENT

Do not take internally. This product is non toxic and non flammable. It does not contain any material with heavy metals such as mercury and lead. Avoid contact with the skin and eyes. Higher concentrations produce more severe irritation. Wear suitable protective clothing such as overalls, goggles, dust masks and gloves. Use barrier cream. Wash splashes from skin or eyes immediately. Ensure adequate ventilation and fresh air entry during application and drying. If there are experiences eye watering, headaches, dizziness or difficulty breathing, leave the area to obtain fresh air or wear respiratory protection. If continued difficulty is experienced, get medical attention immediately. Do not breathe vapor or spray mist. Keep away from food, drink and animal feeding stuffs. Dangerous to fish and other aquatic life. Do not contaminate watercourses or ground. This material and its container must be disposed of in a safe way. Avoid all contact with plant life. Close container after each use and keep out of reach of children. Keep in original container, tightly closed, in cool and dry place. Avoid direct sunlight. Keep from freezing.

This container is used to storage the paint only. Do not apply to surfaces on which food is prepared. Wash hands and exposed skin before meals and after use. Read all safety, security, health and environment precautions before use.

FIRST AID

Eye contact	: Rinse immediately with plenty of clean water. Seek medical advice.
Skin contact	: Wash off thoroughly with plenty of water and soap immediately. Remove contaminated clothing. If irritation occurs, seek medical advice.
Ingestion	: Provide symptomatic treatment and seek medical advice
Inhalation	: Remove person to fresh air, loosen collar and avoid exertion. Keep patient rested and give artificial respiration.

DISCLAIMER

This document contains information issued based on the best and latest of Propan's knowledge in accordance to laboratory testing and practical application experience. The end user must test the product's suitability for their specific application and purpose. Propan shall not be liable for defects where the application of the Product has not been made fully in accordance with the recommendations and requirements. This document is subjected to change without further notice. Please consult Propan for any specific guidance on the suitability of this product for their needs or for any specific application practices.